



Washington State Reference Network

www.wsrn.org



CGSIC – CORS Forum
September 16th, 2008
Savannah, GA

Washington State RTN

- **WSRN (RTN) – Cooperative 90% Coverage**
- **RGPS (RTN) – Dealer / Partnerships 15% Coverage**
- **RGPS (Single Base) – Dealer / Partnerships 20% Coverage**
- **PC3N (RTN) – County Network 5% Coverage**
- **PPI (RTN) – Dealer Network 10% Coverage**



All networks on NAD83 96CORS 2002.00 and all share some station data with WSRN



Washington State Reference Network

Quick Stats

- **90 of 95 Stations Completed**
- **600+ Active Accounts**
- **114,280 Minutes Avg. Monthly Fixed Solutions**
- **NAD83 – 96CORS Epoch 2002.00**
- **Cooperative – Public/Private**
- **70+ Infrastructure Partners**
- **80 Non-Infrastructure (Subscr.)**
- **42 Academic accounts**
- **35 Trainer / Dealer accounts**



Washington State Reference Network

Other Stuff that NGS Wanted Me to Add


- Latencies from CORS to RTN – 0.1 – 1.25 sec. (dependent on connection type)
- Latencies tracked in GPSNet synchronizers and Wireshark
- User Accuracies – 1cm Hz 3cm Vert (Ellipsoid)
- Server pairs; 40+ CORS each, RTN mirrored offsite
- Spacing – 50km – 70km (lowest 30km highest 100km)
- IT – RTN in DMZ, commercial DSL primary connections
- 60% GNSS CORS, full upgrade by 2010




Washington State Reference Network

Real-Time Services


RTCM
Standard
Corrections





VRS



MAC (3Net)



Single-Base



FKP

Washington State Reference Network

Business Model

- **Infrastructure – Partner Funded and Operated**
- **Central Processing Center – Seattle Public Utilities Funded and Operated**
- **Mirror Processing Center – Central Washington University Funded and Operated**
- **Operations Costs Offset by Subscriber Contributions**
 - » *Single Accounts - \$1,900 Annual*
 - » *Five Accounts - \$5,700 Annual*
 - » *Ten Accounts - \$10,000 Annual*
- **Academic and Trainer/Dealer – No Fee**



Washington State Reference Network

Adjustment of WSRN CORS Sites to the National Spatial Reference System

Legacy Method




- 360 Hours Data
- 15 – 24hr OPUS (Extended Output)
- Evaluation Of NGS CORS to Hold
- Network Adjustments – External Software
- 120 Hour Internal Coordinate Monitor Evaluation
- Ongoing Internal Coordinate Monitor Evaluations



*Stations positions are re-computed when out of tolerance
(per Coordinate Monitor, or if any Hardware Changes or
intake/changes to any adjacent stations)*

Washington State Reference Network

Integrity Monitor



Washington State Reference Network

Adjustment of WSRN CORS Sites to the National Spatial Reference System

Integrity Monitor (IM) Method

- 360 Hours Data
- 15 – 24hr OPUS (Extended Output)
- Full Weekly NGS CORS Data
- Integrity Monitor (IM) Weekly on NGS CORS Data (Evaluate CORS to Hold)
- Weekly, Monthly, Quarterly IM PPS Sessions
- 3-Engine Real-Time IM Evaluations (alarms)
- Development of Velocity Data for Transformation Database



Legacy Evaluations will Continue to be Performed

Washington State Reference Network


Adjustment of WSRN CORS Sites **INTO** the National Spatial Reference System

- Height Modernization
- Blue-Booking of 80+ RTN CORS
- OPUS-DB submission of stations
- Submission Of 20+ RTN-CORS to NGS CORS




Height Modernization

Adjustment of WSRN CORS Sites **INTO** the National Spatial Reference System




Height Modernization

Adjustment of WSRN CORS Sites **INTO** the National Spatial Reference System



Washington State Reference Network

Adjustment of WSRN CORS Sites **INTO** the National Spatial Reference System



Washington State Reference Network

Adjustment of WSRN CORS Sites **INTO** the National Spatial Reference System



WSDOT Mount – Walla Walla

This mount will be there for a few years

Washington State Reference Network

Adjustment of WSRN CORS Sites **INTO** the National Spatial Reference System



*LTAH – Latah
Spokane County*

DI3602 DESIGNATION - LTAH CORS ARP

DI3602 PID - DI3602

DI3602 STATE/COUNTY- WA/SPOKANE

DI3602 USGS QUAD - LATAH (1980)

DI3602

DI3602 *CURRENT SURVEY CONTROL

DI3602

DI3602* NAD 83(1986)- 47 16 56. (N) 117 08 50. (W) SCALED

DI3602* NAVD 88 - 754.185 (meters) 2474.36 (feet) ADJUSTED

DI3602

DI3602 GEOID HEIGHT- -18.15 (meters) GEOID03

DI3602 DYNAMIC HT - 754.182 (meters) 2474.35 (feet) COMP

DI3602 MODELED GRAV- 980,583.4 (mgal) NAVD 88

DI3602

DI3602 VERT ORDER - SECOND - CLASS 1



*KOOT - Kootenai
County Airport*

Washington State Reference Network

Adjustment of WSRN CORS Sites **WITH** NGS Marks for Height Modernization




Washington State Reference Network

GIMI – GNSS Integrated Monitoring Initiative




Washington State Reference Network

Localized Effects of Tectonic Movements




Primary Network Monitored by CWU

Washington State Reference Network



Secondary Networks Monitored by WSRN and CWU

Washington State Reference Network



*Individual Stations Monitored for Both Tectonic and
Localized Motion*



Washington State Reference Network

Tolt Dam Study






Washington State Reference Network


Tolt Dam Study



Washington State Reference Network Tolt Dam Study



USGS Seismograph



*Movement and/or Perturbations of the
Ionosphere due to Seismic Events*



Thank You
gavin.schrock@seattle.gov
www.wsrn.org